

**G | SUPPLIED
BY GENIE®**



LIFT WITH CONFIDENCE

ITA HOOK MOUNTED FORKS



ITA Hook Mounted Forks

Genie® has partnered with Cascade™ to provide a complete catalog of all your lift truck hook mounted forks (ITA). Robust design and reliable quality to meet your material handling needs.



Features and Benefits

- Available for standard Class II, III, IV ITA-style carriages
- Available in standard taper (SD) and full taper / polished (TP)
- Manufactured according to the latest ISO standards

More Details

- Free freight on qualifying orders
- Shipping from multiple location in the USA and Canada: minimize lead times
- Popular parts in stock, ship next day.

Tapers



STANDARD TAPER



FULL TAPER & POLISH

Common Part Numbers

By Machine

THICKNESS (IN)	UNIT WIDTH (IN)	UNIT LENGTH (IN)	CAPACITY/PAIR @ LOAD CENTER LBS @ 24"	GENIE PART NUMBER	DESCRIPTION
ITA Class II					
1.125	3	36	2,500	7531274CSD	FORK, ITA, CL2, 3 x 1.125 x 36 SD
1.125	3	42	2,500	7531275CSD	FORK, ITA, CL2, 3 x 1.125 x 42 SD
1.125	3	48	2,500	7531276CSD	FORK, ITA, CL2, 3 x 1.125 x 48 SD
1.50	3	36	4,000	7505743CSD	FORK, ITA, CL2, 3 x 1.5 x 36 SD
1.50	3	42	4,000	7502994CSD	FORK, ITA, CL2, 3 x 1.5 x 42 SD
1.50	3	48	4,000	7502582CSD	FORK, ITA, CL2, 3 x 1.5 x 48 SD
1.50	3	54	4,000	7512588CSD	FORK, ITA, CL2, 3 x 1.5 x 54 SD
1.50	3	60	4,000	7502975CSD	FORK, ITA, CL2, 3 x 1.5 x 60 SD
1.25	4	30	4,000	B2A30SDCSD	FORK, ITA, CL2, 4 x 1.25 x 30 SD
1.25	4	36	4,000	B2A36SDCSD	FORK, ITA, CL2, 4 x 1.25 x 36 SD
1.25	4	42	4,000	B2A42SDCSD	FORK, ITA, CL2, 4 x 1.25 x 42 SD
1.25	4	48	4,000	B2A48SDCSD	FORK, ITA, CL2, 4 x 1.25 x 48 SD
1.25	4	54	4,000	B2A54SDCSD	FORK, ITA, CL2, 4 x 1.25 x 54 SD
1.25	4	60	4,000	B2A60SDCSD	FORK, ITA, CL2, 4 x 1.25 x 60 SD
1.50	4	30	5,500	B2B30SDCSD	FORK, ITA, CL2, 4 x 1.5 x 30 SD
1.50	4	32	5,500	B2B32SDCSD	FORK, ITA, CL2, 4 x 1.5 x 32 SD
1.50	4	36	5,500	B2B36SDCSD	FORK, ITA, CL2, 4 x 1.5 x 36 SD
1.50	4	42	5,500	B2B42SDCSD	FORK, ITA, CL2, 4 x 1.5 x 42 SD
1.50	4	48	5,500	B2B48SDCSD	FORK, ITA, CL2, 4 x 1.5 x 48 SD
1.50	4	54	5,500	B2B54SDCSD	FORK, ITA, CL2, 4 x 1.5 x 54 SD
1.50	4	60	5,500	B2B60SDCSD	FORK, ITA, CL2, 4 x 1.5 x 60 SD
1.50	4	72	5,500	B2B72SDCSD	FORK, ITA, CL2, 4 x 1.5 x 72 SD
1.125	3	36	2,500	7531274CSD	FORK, ITA, CL2, 3 x 1.125 x 36 SD
1.125	3	42	2,500	7531275CSD	FORK, ITA, CL2, 3 x 1.125 x 42 SD
1.125	3	48	2,500	7531276CSD	FORK, ITA, CL2, 3 x 1.125 x 48 SD
1.50	3	36	4,000	7505743CSD	FORK, ITA, CL2, 3 x 1.5 x 36 SD
1.50	3	42	4,000	7502994CSD	FORK, ITA, CL2, 3 x 1.5 x 42 SD

Common Part Numbers

By Machine

THICKNESS (IN)	UNIT WIDTH (IN)	UNIT LENGTH (IN)	CAPACITY/PAIR @ LOAD CENTERLBS @ 24"	GENIE PART NUMBER	DESCRIPTION
1.50	3	48	4,000	7502582CSD	FORK, ITA, CL2, 3 x 1.5 x 48 SD
1.50	3	54	4,000	7512588CSD	FORK, ITA, CL2, 3 x 1.5 x 54 SD
1.50	3	60	4,000	7502975CSD	FORK, ITA, CL2, 3 x 1.5 x 60 SD
1.25	4	30	4,000	B2A30SDCSD	FORK, ITA, CL2, 4 x 1.25 x 30 SD
1.25	4	36	4,000	B2A36SDCSD	FORK, ITA, CL2, 4 x 1.25 x 36 SD
1.25	4	42	4,000	B2A42SDCSD	FORK, ITA, CL2, 4 x 1.25 x 42 SD
1.25	4	48	4,000	B2A48SDCSD	FORK, ITA, CL2, 4 x 1.25 x 48 SD
1.25	4	54	4,000	B2A54SDCSD	FORK, ITA, CL2, 4 x 1.25 x 54 SD
1.25	4	60	4,000	B2A60SDCSD	FORK, ITA, CL2, 4 x 1.25 x 60 SD
1.50	4	30	5,500	B2B30SDCSD	FORK, ITA, CL2, 4 x 1.5 x 30 SD
1.50	4	32	5,500	B2B32SDCSD	FORK, ITA, CL2, 4 x 1.5 x 32 SD
1.50	4	36	5,500	B2B36SDCSD	FORK, ITA, CL2, 4 x 1.5 x 36 SD
1.50	4	42	5,500	B2B42SDCSD	FORK, ITA, CL2, 4 x 1.5 x 42 SD
1.50	4	48	5,500	B2B48SDCSD	FORK, ITA, CL2, 4 x 1.5 x 48 SD
1.50	4	54	5,500	B2B54SDCSD	FORK, ITA, CL2, 4 x 1.5 x 54 SD
1.50	4	60	5,500	B2B60SDCSD	FORK, ITA, CL2, 4 x 1.5 x 60 SD
1.50	4	72	5,500	B2B72SDCSD	FORK, ITA, CL2, 4 x 1.5 x 72 SD
1.50	5	30	5,500	B2C30SDCSD	FORK, ITA, CL2, 5 x 1.5 x 30 SD
1.50	5	36	5,500	B2C36SDCSD	FORK, ITA, CL2, 5 x 1.5 x 36 SD
1.50	5	42	5,500	B2C42SDCSD	FORK, ITA, CL2, 5 x 1.5 x 42 SD
1.50	5	48	5,500	B2C48SDCSD	FORK, ITA, CL2, 5 x 1.5 x 48 SD
1.50	5	54	5,500	B2C54SDCSD	FORK, ITA, CL2, 5 x 1.5 x 54 SD
1.50	5	60	5,500	B2C60SDCSD	FORK, ITA, CL2, 5 x 1.5 x 60 SD
1.50	5	72	5,500	B2C72SDCSD	FORK, ITA, CL2, 5 x 1.5 x 72 SD
1.50	6	30	5,500	B2D30SDCSD	FORK, ITA, CL2, 6 x 1.5 x 30 SD
1.50	6	36	5,500	B2D36SDCSD	FORK, ITA, CL2, 6 x 1.5 x 36 SD
1.50	6	42	5,500	B2D42SDCSD	FORK, ITA, CL2, 6 x 1.5 x 42 SD
1.50	6	48	5,500	B2D48SDCSD	FORK, ITA, CL2, 6 x 1.5 x 48 SD
1.50	6	54	5,500	B2D54SDCSD	FORK, ITA, CL2, 6 x 1.5 x 54 SD

THICKNESS (IN)	UNIT WIDTH (IN)	UNIT LENGTH (IN)	CAPACITY/PAIR @ LOAD CENTERLBS @ 24"	GENIE PART NUMBER	DESCRIPTION
1.50	6	60	5,500	B2D60SDCSD	FORK, ITA, CL2, 6 x 1.5 x 60 SD
1.75	4	30	5,500	B2E30SDCSD	FORK, ITA, CL2, 4 x 1.75 x 30 SD
1.75	4	36	5,500	B2E36SDCSD	FORK, ITA, CL2, 4 x 1.75 x 36 SD
1.75	4	42	5,500	B2E42SDCSD	FORK, ITA, CL2, 4 x 1.75 x 42 SD
1.75	4	48	5,500	B2E48SDCSD	FORK, ITA, CL2, 4 x 1.75 x 48 SD
1.75	4	54	5,500	B2E54SDCSD	FORK, ITA, CL2, 4 x 1.75 x 54 SD
1.75	4	60	5,500	B2E60SDCSD	FORK, ITA, CL2, 4 x 1.75 x 60 SD
1.75	4	72	5,500	B2E72SDCSD	FORK, ITA, CL2, 4 x 1.75 x 72 SD
1.75	4	84	5,500	B2E84SDCSD	FORK, ITA, CL2, 4 x 1.75 x 84 SD
1.75	4	96	5,500	B2E96SDCSD	FORK, ITA, CL2, 4 x 1.75 x 96 SD
1.75	5	30	5,500	B2F30SDCSD	FORK, ITA, CL2, 5 x 1.75 x 30 SD
1.75	5	36	5,500	B2F36SDCSD	FORK, ITA, CL2, 5 x 1.75 x 36 SD
1.75	5	42	5,500	B2F42SDCSD	FORK, ITA, CL2, 5 x 1.75 x 42 SD
1.75	5	48	5,500	B2F48SDCSD	FORK, ITA, CL2, 5 x 1.75 x 48 SD
1.75	5	54	5,500	B2F54SDCSD	FORK, ITA, CL2, 5 x 1.75 x 54 SD
1.75	5	60	5,500	B2F60SDCSD	FORK, ITA, CL2, 5 x 1.75 x 60 SD
1.75	5	72	5,500	B2F72SDCSD	FORK, ITA, CL2, 5 x 1.75 x 72 SD
1.75	5	84	5,500	B2F84SDCSD	FORK, ITA, CL2, 5 x 1.75 x 84 SD
1.75	5	96	5,500	B2F96SDCSD	FORK, ITA, CL2, 5 x 1.75 x 96 SD
1.25	4	30	4,000	B2A30TPCSD	FORK, ITA, CL2, 4 x 1.25 x 30 TP
1.25	4	36	4,000	B2A36TPCSD	FORK, ITA, CL2, 4 x 1.25 x 36 TP
1.25	4	42	4,000	B2A42TPCSD	FORK, ITA, CL2, 4 x 1.25 x 42 TP
1.25	4	48	4,000	B2A48TPCSD	FORK, ITA, CL2, 4 x 1.25 x 48 TP
1.25	4	54	4,000	B2A54TPCSD	FORK, ITA, CL2, 4 x 1.25 x 54 TP
1.25	4	60	4,000	B2A60TPCSD	FORK, ITA, CL2, 4 x 1.25 x 60 TP
1.50	4	30	5,500	B2B30TPCSD	FORK, ITA, CL2, 4 x 1.5 x 30 TP
1.50	4	32	5,500	B2B32TPCSD	FORK, ITA, CL2, 4 x 1.5 x 32 TP
1.50	4	36	5,500	B2B36TPCSD	FORK, ITA, CL2, 4 x 1.5 x 36 TP
1.50	4	42	5,500	B2B42TPCSD	FORK, ITA, CL2, 4 x 1.5 x 42 TP

Common Part Numbers

By Machine

THICKNESS (IN)	UNIT WIDTH (IN)	UNIT LENGTH (IN)	CAPACITY/PAIR @ LOAD CENTERLBS @ 24"	GENIE PART NUMBER	DESCRIPTION
1.50	4	48	5,500	B2B48TPCSD	FORK, ITA, CL2, 4 x 1.5 x 48 TP
1.50	4	54	5,500	B2B54TPCSD	FORK, ITA, CL2, 4 x 1.5 x 54 TP
1.50	4	60	5,500	B2B60TPCSD	FORK, ITA, CL2, 4 x 1.5 x 60 TP
1.50	5	30	5,500	B2C30TPCSD	FORK, ITA, CL2, 5 x 1.5 x 30 TP
1.50	5	36	5,500	B2C36TPCSD	FORK, ITA, CL2, 5 x 1.5 x 36 TP
1.50	5	42	5,500	B2C42TPCSD	FORK, ITA, CL2, 5 x 1.5 x 42 TP
1.50	5	48	5,500	B2C48TPCSD	FORK, ITA, CL2, 5 x 1.5 x 48 TP
1.50	5	54	5,500	B2C54TPCSD	FORK, ITA, CL2, 5 x 1.5 x 54 TP
1.50	5	60	5,500	B2C60TPCSD	FORK, ITA, CL2, 5 x 1.5 x 60 TP
1.50	6	30	5,500	B2D30TPCSD	FORK, ITA, CL2, 6 x 1.5 x 30 TP
1.50	6	36	5,500	B2D36TPCSD	FORK, ITA, CL2, 6 x 1.5 x 36 TP
1.50	6	42	5,500	B2D42TPCSD	FORK, ITA, CL2, 6 x 1.5 x 42 TP
1.50	6	48	5,500	B2D48TPCSD	FORK, ITA, CL2, 6 x 1.5 x 48 TP
1.50	6	54	5,500	B2D54TPCSD	FORK, ITA, CL2, 6 x 1.5 x 54 TP
1.50	6	60	5,500	B2D60TPCSD	FORK, ITA, CL2, 6 x 1.5 x 60 TP
1.75	4	30	5,500	B2E30TPCSD	FORK, ITA, CL2, 4 x 1.75 x 30 TP
1.75	4	36	5,500	B2E36TPCSD	FORK, ITA, CL2, 4 x 1.75 x 36 TP
1.75	4	42	5,500	B2E42TPCSD	FORK, ITA, CL2, 4 x 1.75 x 42 TP
1.75	4	48	5,500	B2E48TPCSD	FORK, ITA, CL2, 4 x 1.75 x 48 TP
1.75	4	54	5,500	B2E54TPCSD	FORK, ITA, CL2, 4 x 1.75 x 54 TP
1.75	4	60	5,500	B2E60TPCSD	FORK, ITA, CL2, 4 x 1.75 x 60 TP
1.75	4	72	5,500	B2E72TPCSD	FORK, ITA, CL2, 4 x 1.75 x 72 TP
1.75	5	30	5,500	B2F30TPCSD	FORK, ITA, CL2, 5 x 1.75 x 30 TP
1.75	5	36	5,500	B2F36TPCSD	FORK, ITA, CL2, 5 x 1.75 x 36 TP
1.75	5	42	5,500	B2F42TPCSD	FORK, ITA, CL2, 5 x 1.75 x 42 TP
1.75	5	48	5,500	B2F48TPCSD	FORK, ITA, CL2, 5 x 1.75 x 48 TP
1.75	5	54	5,500	B2F54TPCSD	FORK, ITA, CL2, 5 x 1.75 x 54 TP
1.75	5	60	5,500	B2F60TPCSD	FORK, ITA, CL2, 5 x 1.75 x 60 TP
1.75	5	72	5,500	B2F72TPCSD	FORK, ITA, CL2, 5 x 1.75 x 72 TP

THICKNESS (IN)	UNIT WIDTH (IN)	UNIT LENGTH (IN)	CAPACITY/PAIR @ LOAD CENTERLBS @ 24"	GENIE PART NUMBER	DESCRIPTION
ITA Class III					
1.50	6	42	8,000	B3D42SDCSD	FORK, ITA, CL3, 6 x 1.5 x 42 SD
1.50	6	48	8,000	B3D48SDCSD	FORK, ITA, CL3, 6 x 1.5 x 48 SD
1.50	6	54	8,000	B3D54SDCSD	FORK, ITA, CL3, 6 x 1.5 x 54 SD
1.50	6	60	8,000	B3D60SDCSD	FORK, ITA, CL3, 6 x 1.5 x 60 SD
1.50	7	42	9,600	B3J42SDCSD	FORK, ITA, CL3, 7 x 1.5 x 42 SD
1.50	7	48	9,600	B3J48SDCSD	FORK, ITA, CL3, 7 x 1.5 x 48 SD
1.50	7	54	9,600	B3J54SDCSD	FORK, ITA, CL3, 7 x 1.5 x 54 SD
1.50	7	60	9,600	B3J60SDCSD	FORK, ITA, CL3, 7 x 1.5 x 60 SD
1.50	8	42	10,000	B3K42SDCSD	FORK, ITA, CL3, 8 x 1.5 x 42 SD
1.50	8	48	10,000	B3K48SDCSD	FORK, ITA, CL3, 8 x 1.5 x 48 SD
1.50	8	54	10,000	B3K54SDCSD	FORK, ITA, CL3, 8 x 1.5 x 54 SD
1.50	8	60	10,000	B3K60SDCSD	FORK, ITA, CL3, 8 x 1.5 x 60 SD
1.75	5	36	8,200	B3F36SDCSD	FORK, ITA, CL3, 5 x 1.75 x 36 SD
1.75	5	42	8,200	B3F42SDCSD	FORK, ITA, CL3, 5 x 1.75 x 42 SD
1.75	5	48	8,200	B3F48SDCSD	FORK, ITA, CL3, 5 x 1.75 x 48 SD
1.75	5	54	8,200	B3F54SDCSD	FORK, ITA, CL3, 5 x 1.75 x 54 SD
1.75	5	60	8,200	B3F60SDCSD	FORK, ITA, CL3, 5 x 1.75 x 60 SD
1.75	5	72	8,200	B3F72SDCSD	FORK, ITA, CL3, 5 x 1.75 x 72 SD
1.75	5	84	8,200	B3F84SDCSD	FORK, ITA, CL3, 5 x 1.75 x 84 SD
1.75	5	96	8,200	B3F96SDCSD	FORK, ITA, CL3, 5 x 1.75 x 96 SD
1.75	7	42	10,000	B3L42SDCSD	FORK, ITA, CL3, 7 x 1.75 x 42 SD
1.75	7	48	10,000	B3L48SDCSD	FORK, ITA, CL3, 7 x 1.75 x 48 SD
1.75	7	54	10,000	B3L54SDCSD	FORK, ITA, CL3, 7 x 1.75 x 54 SD
1.75	7	60	10,000	B3L60SDCSD	FORK, ITA, CL3, 7 x 1.75 x 60 SD
1.75	7	72	10,000	B3L72SDCSD	FORK, ITA, CL3, 7 x 1.75 x 72 SD
2.00	4	42	8,400	B3H42SDCSD	FORK, ITA, CL3, 4 x 2 x 42 SD
2.00	4	48	8,400	B3H48SDCSD	FORK, ITA, CL3, 4 x 2 x 48 SD
2.00	4	54	8,400	B3H54SDCSD	FORK, ITA, CL3, 4 x 2 x 54 SD
2.00	4	60	8,400	B3H60SDCSD	FORK, ITA, CL3, 4 x 2 x 60 SD

Common Part Numbers

By Machine

THICKNESS (IN)	UNIT WIDTH (IN)	UNIT LENGTH (IN)	CAPACITY/PAIR @ LOAD CENTERLBS @ 24"	GENIE PART NUMBER	DESCRIPTION
2.00	4	72	8,400	B3H72SDCSD	FORK, ITA, CL3, 4 x 2 x 72 SD
2.00	5	36	10,000	B3M36SDCSD	FORK, ITA, CL3, 5 x 2 x 36 SD
2.00	5	42	10,000	B3M42SDCSD	FORK, ITA, CL3, 5 x 2 x 42 SD
2.00	5	48	10,000	B3M48SDCSD	FORK, ITA, CL3, 5 x 2 x 48 SD
2.00	5	54	10,000	B3M54SDCSD	FORK, ITA, CL3, 5 x 2 x 54 SD
2.00	5	60	10,000	B3M60SDCSD	FORK, ITA, CL3, 5 x 2 x 60 SD
2.00	5	72	10,000	B3M72SDCSD	FORK, ITA, CL3, 5 x 2 x 72 SD
2.00	5	84	10,000	B3M84SDCSD	FORK, ITA, CL3, 5 x 2 x 84 SD
2.00	5	96	10,000	B3M96SDCSD	FORK, ITA, CL3, 5 x 2 x 96 SD
2.00	6	36	10,000	B3N36SDCSD	FORK, ITA, CL3, 6 x 2 x 36 SD
2.00	6	42	10,000	B3N42SDCSD	FORK, ITA, CL3, 6 x 2 x 42 SD
2.00	6	48	10,000	B3N48SDCSD	FORK, ITA, CL3, 6 x 2 x 48 SD
2.00	6	54	10,000	B3N54SDCSD	FORK, ITA, CL3, 6 x 2 x 54 SD
2.00	6	60	10,000	B3N60SDCSD	FORK, ITA, CL3, 6 x 2 x 60 SD
2.00	6	72	10,000	B3N72SDCSD	FORK, ITA, CL3, 6 x 2 x 72 SD
2.00	6	84	10,000	B3N84SDCSD	FORK, ITA, CL3, 6 x 2 x 84 SD
2.00	6	96	10,000	B3N96SDCSD	FORK, ITA, CL3, 6 x 2 x 96 SD
1.50	6	42	8,000	B3D42TPCSD	FORK, ITA, CL3, 6 x 1.5 x 42 TP
1.50	6	48	8,000	B3D48TPCSD	FORK, ITA, CL3, 6 x 1.5 x 48 TP
1.50	6	54	8,000	B3D54TPCSD	FORK, ITA, CL3, 6 x 1.5 x 54 TP
1.50	6	60	8,000	B3D60TPCSD	FORK, ITA, CL3, 6 x 1.5 x 60 TP
1.50	7	42	9,600	B3J42TPCSD	FORK, ITA, CL3, 7 x 1.5 x 42 TP
1.50	7	48	9,600	B3J48TPCSD	FORK, ITA, CL3, 7 x 1.5 x 48 TP
1.50	7	54	9,600	B3J54TPCSD	FORK, ITA, CL3, 7 x 1.5 x 54 TP
1.50	7	60	9,600	B3J60TPCSD	FORK, ITA, CL3, 7 x 1.5 x 60 TP
1.50	8	42	10,000	B3K42TPCSD	FORK, ITA, CL3, 8 x 1.5 x 42 TP
1.50	8	48	10,000	B3K48TPCSD	FORK, ITA, CL3, 8 x 1.5 x 48 TP
1.50	8	54	10,000	B3K54TPCSD	FORK, ITA, CL3, 8 x 1.5 x 54 TP
1.50	8	60	10,000	B3K60TPCSD	FORK, ITA, CL3, 8 x 1.5 x 60 TP

THICKNESS (IN)	UNIT WIDTH (IN)	UNIT LENGTH (IN)	CAPACITY/PAIR @ LOAD CENTERLBS @ 24"	GENIE PART NUMBER	DESCRIPTION
1.75	5	36	8,200	B3F36TPCSD	FORK, ITA, CL3, 5 x 1.75 x 36 TP
1.75	5	42	8,200	B3F42TPCSD	FORK, ITA, CL3, 5 x 1.75 x 42 TP
1.75	5	48	8,200	B3F48TPCSD	FORK, ITA, CL3, 5 x 1.75 x 48 TP
1.75	5	54	8,200	B3F54TPCSD	FORK, ITA, CL3, 5 x 1.75 x 54 TP
1.75	5	60	8,200	B3F60TPCSD	FORK, ITA, CL3, 5 x 1.75 x 60 TP
1.75	5	72	8,200	B3F72TPCSD	FORK, ITA, CL3, 5 x 1.75 x 72 TP
1.75	5	84	8,200	B3F84TPCSD	FORK, ITA, CL3, 5 x 1.75 x 84 TP
1.75	5	96	8,200	B3F96TPCSD	FORK, ITA, CL3, 5 x 1.75 x 96 TP
1.75	7	42	10,000	B3L42TPCSD	FORK, ITA, CL3, 7 x 1.75 x 42 TP
1.75	7	48	10,000	B3L48TPCSD	FORK, ITA, CL3, 7 x 1.75 x 48 TP
1.75	7	54	10,000	B3L54TPCSD	FORK, ITA, CL3, 7 x 1.75 x 54 TP
1.75	7	60	10,000	B3L60TPCSD	FORK, ITA, CL3, 7 x 1.75 x 60 TP
1.75	7	72	10,000	B3L72TPCSD	FORK, ITA, CL3, 7 x 1.75 x 72 TP
2.00	5	36	10,000	B3M36TPCSD	FORK, ITA, CL3, 5 x 2 x 36 TP
2.00	5	42	10,000	B3M42TPCSD	FORK, ITA, CL3, 5 x 2 x 42 TP
2.00	5	48	10,000	B3M48TPCSD	FORK, ITA, CL3, 5 x 2 x 48 TP
2.00	5	54	10,000	B3M54TPCSD	FORK, ITA, CL3, 5 x 2 x 54 TP
2.00	5	60	10,000	B3M60TPCSD	FORK, ITA, CL3, 5 x 2 x 60 TP
2.00	5	72	10,000	B3M72TPCSD	FORK, ITA, CL3, 5 x 2 x 72 TP
2.00	5	84	10,000	B3M84TPCSD	FORK, ITA, CL3, 5 x 2 x 84 TP
2.00	5	96	10,000	B3M96TPCSD	FORK, ITA, CL3, 5 x 2 x 96 TP
2.00	6	36	10,000	B3N36TPCSD	FORK, ITA, CL3, 6 x 2 x 36 TP
2.00	6	42	10,000	B3N42TPCSD	FORK, ITA, CL3, 6 x 2 x 42 TP
2.00	6	48	10,000	B3N48TPCSD	FORK, ITA, CL3, 6 x 2 x 48 TP
2.00	6	54	10,000	B3N54TPCSD	FORK, ITA, CL3, 6 x 2 x 54 TP
2.00	6	60	10,000	B3N60TPCSD	FORK, ITA, CL3, 6 x 2 x 60 TP
2.00	6	72	10,000	B3N72TPCSD	FORK, ITA, CL3, 6 x 2 x 72 TP
2.00	6	84	10,000	B3N84TPCSD	FORK, ITA, CL3, 6 x 2 x 84 TP
2.00	6	96	10,000	B3N96TPCSD	FORK, ITA, CL3, 6 x 2 x 96 TP

Common Part Numbers

By Machine

THICKNESS (IN)	UNIT WIDTH (IN)	UNIT LENGTH (IN)	CAPACITY/PAIR @ LOAD CENTERLBS @ 24"	GENIE PART NUMBER	DESCRIPTION
ITA Class IV					
1.50	10	42	13,400	7502951CSD	FORK, ITA, CL4, 10 x 1.5 x 42 TP
1.50	10	48	13,400	7500087CSD	FORK, ITA, CL4, 10 x 1.5 x 48 TP
1.50	10	54	13,400	7504627CSD	FORK, ITA, CL4, 10 x 1.5 x 54 TP
1.50	10	60	13,400	7505837CSD	FORK, ITA, CL4, 10 x 1.5 x 60 TP
1.50	10	72	13,400	7509309CSD	FORK, ITA, CL4, 10 x 1.5 x 72 TP
1.50	12	42	16,200	7507782CSD	FORK, ITA, CL4, 12 x 1.5 x 42 TP
1.50	12	48	16,200	7500240CSD	FORK, ITA, CL4, 12 x 1.5 x 48 TP
1.50	12	54	16,200	7527928CSD	FORK, ITA, CL4, 12 x 1.5 x 54 TP
1.50	12	60	16,200	7508018CSD	FORK, ITA, CL4, 12 x 1.5 x 60 TP
2.00	6	42	12,600	B4N42SDCSD	FORK, ITA, CL4, 6 x 2 x 42 SD
2.00	6	48	12,600	B4N48SDCSD	FORK, ITA, CL4, 6 x 2 x 48 SD
2.00	6	54	12,600	B4N54SDCSD	FORK, ITA, CL4, 6 x 2 x 54 SD
2.00	6	60	12,600	B4N60SDCSD	FORK, ITA, CL4, 6 x 2 x 60 SD
2.00	6	72	12,600	B4N72SDCSD	FORK, ITA, CL4, 6 x 2 x 72 SD
2.00	7	42	15,200	B4P42SDCSD	FORK, ITA, CL4, 7 x 2 x 42 SD
2.00	7	48	15,200	B4P48SDCSD	FORK, ITA, CL4, 7 x 2 x 48 SD
2.00	7	54	15,200	B4P54SDCSD	FORK, ITA, CL4, 7 x 2 x 54 SD
2.00	7	60	15,200	B4P60SDCSD	FORK, ITA, CL4, 7 x 2 x 60 SD
2.00	7	72	15,200	B4P72SDCSD	FORK, ITA, CL4, 7 x 2 x 72 SD
2.00	7	84	15,200	B4P84SDCSD	FORK, ITA, CL4, 7 x 2 x 84 SD
2.00	7	96	15,200	B4P96SDCSD	FORK, ITA, CL4, 7 x 2 x 96 SD
2.00	8	42	16,800	B4Q42SDCSD	FORK, ITA, CL4, 8 x 2 x 42 SD
2.00	8	48	16,800	B4Q48SDCSD	FORK, ITA, CL4, 8 x 2 x 48 SD
2.00	8	54	16,800	B4Q54SDCSD	FORK, ITA, CL4, 8 x 2 x 54 SD
2.00	8	60	16,800	B4Q60SDCSD	FORK, ITA, CL4, 8 x 2 x 60 SD
2.00	8	72	16,800	B4Q72SDCSD	FORK, ITA, CL4, 8 x 2 x 72 SD
2.00	8	84	16,800	B4Q84SDCSD	FORK, ITA, CL4, 8 x 2 x 84 SD
2.00	8	96	16,800	B4Q96SDCSD	FORK, ITA, CL4, 8 x 2 x 96 SD

THICKNESS (IN)	UNIT WIDTH (IN)	UNIT LENGTH (IN)	CAPACITY/PAIR @ LOAD CENTERLBS @ 24"	GENIE PART NUMBER	DESCRIPTION
2.25	6	42	17,500	B4R42SDCSD	FORK, ITA, CL4, 6 x 2.25 x 42 SD
2.25	6	48	17,500	B4R48SDCSD	FORK, ITA, CL4, 6 x 2.25 x 48 SD
2.25	6	54	17,500	B4R54SDCSD	FORK, ITA, CL4, 6 x 2.25 x 54 SD
2.25	6	60	17,500	B4R60SDCSD	FORK, ITA, CL4, 6 x 2.25 x 60 SD
2.25	6	72	17,500	B4R72SDCSD	FORK, ITA, CL4, 6 x 2.25 x 72 SD
2.25	6	84	17,500	B4R84SDCSD	FORK, ITA, CL4, 6 x 2.25 x 84 SD
2.25	6	96	17,500	B4R96SDCSD	FORK, ITA, CL4, 6 x 2.25 x 96 SD
2.50	6	42	17,500	B4T42SDCSD	FORK, ITA, CL4, 6 x 2.5 x 42 SD
2.50	6	48	17,500	B4T48SDCSD	FORK, ITA, CL4, 6 x 2.5 x 48 SD
2.50	6	54	17,500	B4T54SDCSD	FORK, ITA, CL4, 6 x 2.5 x 54 SD
2.50	6	60	17,500	B4T60SDCSD	FORK, ITA, CL4, 6 x 2.5 x 60 SD
2.50	6	72	17,500	B4T72SDCSD	FORK, ITA, CL4, 6 x 2.5 x 72 SD
2.50	6	84	17,500	B4T84SDCSD	FORK, ITA, CL4, 6 x 2.5 x 84 SD
2.50	6	96	17,500	B4T96SDCSD	FORK, ITA, CL4, 6 x 2.5 x 96 SD
2.00	6	42	12,600	B4N42TPCSD	FORK, ITA, CL4, 6 x 2 x 42 TP
2.00	6	48	12,600	B4N48TPCSD	FORK, ITA, CL4, 6 x 2 x 48 TP
2.00	6	54	12,600	B4N54TPCSD	FORK, ITA, CL4, 6 x 2 x 54 TP
2.00	6	60	12,600	B4N60TPCSD	FORK, ITA, CL4, 6 x 2 x 60 TP
2.00	6	72	12,600	B4N72TPCSD	FORK, ITA, CL4, 6 x 2 x 72 TP
2.00	7	42	15,200	B4P42TPCSD	FORK, ITA, CL4, 7 x 2 x 42 TP
2.00	7	48	15,200	B4P48TPCSD	FORK, ITA, CL4, 7 x 2 x 48 TP
2.00	7	54	15,200	B4P54TPCSD	FORK, ITA, CL4, 7 x 2 x 54 TP
2.00	7	60	15,200	B4P60TPCSD	FORK, ITA, CL4, 7 x 2 x 60 TP
2.00	7	72	15,200	B4P72TPCSD	FORK, ITA, CL4, 7 x 2 x 72 TP
2.00	7	84	15,200	B4P84TPCSD	FORK, ITA, CL4, 7 x 2 x 84 TP
2.00	7	96	15,200	B4P96TPCSD	FORK, ITA, CL4, 7 x 2 x 96 TP
2.00	8	42	16,800	B4Q42TPCSD	FORK, ITA, CL4, 8 x 2 x 42 TP
2.00	8	48	16,800	B4Q48TPCSD	FORK, ITA, CL4, 8 x 2 x 48 TP
2.00	8	54	16,800	B4Q54TPCSD	FORK, ITA, CL4, 8 x 2 x 54 TP

Common Part Numbers

By Machine

THICKNESS (IN)	UNIT WIDTH (IN)	UNIT LENGTH (IN)	CAPACITY/PAIR @ LOAD CENTERLBS @ 24"	GENIE PART NUMBER	DESCRIPTION
2.00	8	60	16,800	B4Q60TPCSD	FORK, ITA, CL4, 8 x 2 x 60 TP
2.00	8	72	16,800	B4Q72TPCSD	FORK, ITA, CL4, 8 x 2 x 72 TP
2.00	8	84	16,800	B4Q84TPCSD	FORK, ITA, CL4, 8 x 2 x 84 TP
2.00	8	96	16,800	B4Q96TPCSD	FORK, ITA, CL4, 8 x 2 x 96 TP
2.25	6	42	17,500	B4R42TPCSD	FORK, ITA, CL4, 6 x 2.25 x 42 TP
2.25	6	48	17,500	B4R48TPCSD	FORK, ITA, CL4, 6 x 2.25 x 48 TP
2.25	6	54	17,500	B4R54TPCSD	FORK, ITA, CL4, 6 x 2.25 x 54 TP
2.25	6	60	17,500	B4R60TPCSD	FORK, ITA, CL4, 6 x 2.25 x 60 TP
2.25	6	72	17,500	B4R72TPCSD	FORK, ITA, CL4, 6 x 2.25 x 72 TP
2.25	6	84	17,500	B4R84TPCSD	FORK, ITA, CL4, 6 x 2.25 x 84 TP
2.25	6	96	17,500	B4R96TPCSD	FORK, ITA, CL4, 6 x 2.25 x 96 TP
2.50	6	42	17,500	B4T42TPCSD	FORK, ITA, CL4, 6 x 2.5 x 42 TP
2.50	6	48	17,500	B4T48TPCSD	FORK, ITA, CL4, 6 x 2.5 x 48 TP
2.50	6	54	17,500	B4T54TPCSD	FORK, ITA, CL4, 6 x 2.5 x 54 TP
2.50	6	60	17,500	B4T60TPCSD	FORK, ITA, CL4, 6 x 2.5 x 60 TP
2.50	6	72	17,500	B4T72TPCSD	FORK, ITA, CL4, 6 x 2.5 x 72 TP
2.50	6	84	17,500	B4T84TPCSD	FORK, ITA, CL4, 6 x 2.5 x 84 TP
2.50	6	96	17,500	B4T96TPCSD	FORK, ITA, CL4, 6 x 2.5 x 96 TP
ITA Forks Extensions					
	4	48		7000050CSD	FORK, ITA, EXTEND, 4"x 48"
	4	54		7000051CSD	FORK, ITA, EXTEND, 4"x 54"
	4	60		7000052CSD	FORK, ITA, EXTEND, 4"x 60"
	4	63		7000053CSD	FORK, ITA, EXTEND, 4"x 63"
	4	66		7000054CSD	FORK, ITA, EXTEND, 4"x 66"
	4	72		7000056CSD	FORK, ITA, EXTEND, 4"x 72"
	4	84		7000057CSD	FORK, ITA, EXTEND, 4"x 84"
	4	90		7005104CSD	FORK, ITA, EXTEND, 4"x 90"
	4	96		7000058CSD	FORK, ITA, EXTEND, 4"x 96"

THICKNESS (IN)	UNIT WIDTH (IN)	UNIT LENGTH (IN)	CAPACITY/PAIR @ LOAD CENTERLBS @ 24"	GENIE PART NUMBER	DESCRIPTION
	5	48		7000059CSD	FORK, ITA, EXTEND, 5"x 48"
	5	54		7000060CSD	FORK, ITA, EXTEND, 5"x 54"
	5	60		7000061CSD	FORK, ITA, EXTEND, 5"x 60"
	5	63		7000062CSD	FORK, ITA, EXTEND, 5"x 63"
	5	66		7000063CSD	FORK, ITA, EXTEND, 5"x 66"
	5	72		7000064CSD	FORK, ITA, EXTEND, 5"x 72"
	5	84		7000065CSD	FORK, ITA, EXTEND, 5"x 84"
	5	90		7004318CSD	FORK, ITA, EXTEND, 5"x 90"
	5	96		7000066CSD	FORK, ITA, EXTEND, 5"x 96"
	6	48		7000067CSD	FORK, ITA, EXTEND, 6"x 48"
	6	54		7000068CSD	FORK, ITA, EXTEND, 6"x 54"
	6	60		7000069CSD	FORK, ITA, EXTEND, 6"x 60"
	6	72		7000070CSD	FORK, ITA, EXTEND, 6"x 72"
	6	84		7000071CSD	FORK, ITA, EXTEND, 6"x 84"
	6	90		7001456CSD	FORK, ITA, EXTEND, 6"x 90"
	6	96		7000073CSD	FORK, ITA, EXTEND, 6"x 96"
	7	54		7000074CSD	FORK, ITA, EXTEND, 7"x 54"
	7	72		7000075CSD	FORK, ITA, EXTEND, 7"x 72"
	7	96		7000076CSD	FORK, ITA, EXTEND, 7"x 96"
ITA Pin Kit					
				7000031CSD	FORK, ITA, PIN KIT, CL2 1/2"
				7000040CSD	FORK, ITA, PIN KIT, CL2 5/8"
				7000032CSD	FORK, ITA, PIN KIT, CL3 1/2"
				7000042CSD	FORK, ITA, PIN KIT, CL3 5/8"
				7000033CSD	FORK, ITA, PIN KIT, CL4 1/2"
				7000045CSD	FORK, ITA, PIN KIT, CL4 5/8"

Common Part Numbers

By Machine

THICKNESS (IN)	UNIT WIDTH (IN)	UNIT LENGTH (IN)	CAPACITY/PAIR @ LOAD CENTERLBS @ 24"	GENIE PART NUMBER	DESCRIPTION
ITA Blocks					
	1.5	42		B2015422CSD	FORK, ITA BLOCK, CL2, 1.5 x 2 x 42 SD
	1.5	48		B2015482CSD	FORK, ITA BLOCK, CL2, 1.5 x 2 x 48 SD
	2	42		B2020422CSD	FORK, ITA BLOCK, CL2, 2 x 2 x 42 SD
	2	48		B2020482CSD	FORK, ITA BLOCK, CL2, 2 x 2 x 48 SD
	1.5	42		B2015423CSD	FORK, ITA BLOCK, CL3, 1.5 x 2 x 42 SD
	1.5	48		B2015483CSD	FORK, ITA BLOCK, CL3, 1.5 x 2 x 48 SD
	2	42		B2020423CSD	FORK, ITA BLOCK, CL3, 2 x 2 x 42 SD
	2	48		B2020483CSD	FORK, ITA BLOCK, CL3, 2 x 2 x 48 SD

Worldwide Manufacturing And Distribution

Australia · Brazil · Caribbean · Central America · China · France · Germany · Italy · Japan · Korea · Mexico
Southeast Asia · Spain · Sweden · United Arab Emirates · United Kingdom · United States

Toll Free in USA/Canada **+1 (800) 536-1800** · Telephone **+1 (425) 881-1800** · Fax +1 (425) 883-3475

6464 185th Ave. NE, Redmond, WA 98052

Effective Date: December, 2020. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Terex Corporation, Terex, Genie and Quality By Design are trademarks of Terex Corporation or its subsidiaries. © 2021 Terex Corporation. GPB 3K 0109M. Part No. 109305.



GM109305