

# LONG-TERM SAVINGS

## GENIE® BATTERY CHARGE INDICATOR (BCI) AND LOW VOLTAGE INTERRUPT (LVI) FOR ELECTRIC BOOMS\*

### FEATURES



Visible  
Battery Details



Minimize Total  
Cost of Ownership



Optimal  
Battery Life



### BCI BENEFITS

- ⊕ Protects against unnecessary downtime due to lack of battery charge
- ⊕ From the platform, easily see the amount of charge remaining

### LVI BENEFITS

- ⊕ Prevents costly battery replacements caused by damaging battery drainage
- ⊕ Limits boom functions at a pre-set low voltage point for added battery protection

OPTION OR STANDARD	AVAILABLE ON
Option	Z®-30/20N, Z-34/22 DC, Z-34/22N, Z-45/25 DC (legacy model)
Standard	Z-33/18, Z-40/23N, Z-45 DC (FE based), Z-60 DC

\*LVI pictured above. Functionality differs based on whether these options are standard on the machine or added as an option. Please refer to the above chart to determine what models have these as standard and what models have these as an option.

**Genie**  
A TEREX BRAND

**QUALITY** BY DESIGN

ORDER AT [GOGENEILIFT.COM](http://GOGENEILIFT.COM)