

GENIE® PROTECTIVE SOLUTION



LIFT A GUARD FALL ARREST BAR

GENIE® PROTECTIVE SOLUTION FOR OPERATORS



LIFT A GUARD ARREST

USE YOUR GENIE® BOOM LIFT AS A FALL ARREST ANCHOR

There can be times when a worker needs to perform his necessary tasks from an adjacent structure to the platform. This new system enables the worker to use his Genie boom lift as a fall arrest anchor while remaining connected to the platform, benefiting from a greater working area to move around in.

Featuring a smooth, sliding, horizontal track design, the Genie[®] Fall Arrest Bar accessory, available for either 1.83 m (6 ft) or 2.44 m (8 ft) platforms, can be fitted to nearly all Genie booms and is compliant with European requirements*.

You can order the Genie Fall Arrest Bar by visiting gogenielift.com • - Fall Arrest Bar for 1.83 m (6 ft) platforms: Part Number 1261023GT - Fall Arrest Bar for 2.44 m (8 ft) platforms: Part Number 1261022GT





*Jobsite and local restrictions may apply. For further information on use, please see our Operator's Manual.



HOW DOES IT WORK?

- Provides a smooth, sliding, horizontal track that allows users to tie off and move freely outside the platform using a 1.83 m (6 ft) shock-absorbing lanyard.
- The enclosed track, made from high strength steel, protects the trolley from weather and debris.
- The yellow, identifiable bar attaches quickly and easily, within 15 minutes, for fast setup and removal.
- This feature also allows the bar to be transferred easily among many lifts, providing flexibility for teams who manage multiple lifts in one fleet.



© 2018 Terex Corporation. Terex, Genie and Taking You Higher are trademarks of Terex Corporation or its subsidiaries.